ROGUE

HOW TO UPDATE FIRMWARE - ANDROID DEVICE

This guides shows how to install the Sunrise OTA App and update firmware on your Curve LTG Treadmill.

Written By: Rogue Product Development



Step 1 — How to Update Firmware - Android Device



 Download the "anplus-ota" from play store and install to the cell phone or portable device with Bluetooth as shown. Make sure the cell phone or portable device can receive email as the update program will be sent to the email as a *.bin format email attachment.



- Start walking on treadmill. Running belt MUST be moving at 2mph or higher during the entirety of the OTA update (4 Minutes) Keep walking.
- Press and hold (approximately 5 seconds) "-", "+" and "PAUSE/STOP" key at the same time to enter the OTA update mode as shown in Image 2, Lettering "OTA" and Bluetooth icon shows on the screen as shown in Image OR screen will be flashing.

Step 3



• Open the App on your mobile device and click the "START " button to enter the OTA process.

Step 4

= Annis Help	
Follow the belowing steps to update	
1	
Step1: Choose a device to be paired	
SCAN BLUETOOTH	J
Step2: Load the updated file	
3	
Step3: Update device	
START TO UPDATE	
QUIT	
\triangleleft 0 \Box	
Choose a device for pairing	
* Turn on bluetooth	
Pair a device	
Official and a strategy first to account	
Click the belowing list to connect	
Available device	
SF-T722068	
HUAWEI Band 6-076 F4:87:C5:8E:80:76	
D1531155	
• 04:91:62:21:D3:0D	
F63 F5:C0:00:0C:5F:D7	
null 68:39:43:45:78:CE	
= 00.37.43.43.70.CE	
TAILG-1f61	
Rescan(9)	

- Click "Scan Bluetooth". Make sure the Bluetooth is turned on on your mobile device.
- You will see surrounding Bluetooth devices. (If you can't see, click the "Refresh" key below to re-scan), find the Console's Bluetooth name as "F63" in the device list
- Once pairing is successful, proceed to Step 5.

Step 5

E HELP
Follow the belowing steps to update
Re-pair
Step1: Choose a device to be paired OK
F63 F5:C0:00:0C:5F:D7
~
2
Step2: Load the updated file
START TO LOAD
3
Step3: Update device
START TO UPDATE

				QUIT
	\triangleleft	0		
< AA	02170T1-23	🖸	Pť	j
	1925558935 smartjet14 ~	22:00		@1
				20
-	eent(1) Save 70T1-23 /10-90f7 .0К У	all		-
¢	Reply	¢	orward	
	\triangleleft	0		
	02170T1-23 192555893 smartjet14 ~		PI	
AA021	170T1-230227	7_V10-90f	6271 14321	b47.bin
		Save		
	Save 1	attachr	ments	
	1	Forward		
		Share		
		Cancel		

- Click the "Start to Load" button.
- If your Inbox appears empty, you will need to import the updated file into the inbox now.
- Open your email app on the cell phone or portable device, locate the email with the *.bin attachment. Click the attachment (Image 2) then long press the *.bin attachment to show "save" option, then click "Save" to save to the cell phone or portable device.

Step 6



 Select the directory and click the "SAVE" key to save the update file for later access

Step 7



- Click the "Start to Update" button, the app will begin displaying progress. Wait for roughly 3 minutes and make sure the Console is in power.
- When the app shows "100%" updated, the screen jumps back to the original screen from Step 3, meanwhile the console beeps and automatically restarts.
- Firmware update is complete

HELP
Follow the belowing steps to update
Re-pair
Step1: Choose a device to be paired OK
F63 F5:C0:00:0C:5F:D7
Re-load
Step2: Load the updated Tile OK AA02170T1-230227_V10-90f627b 4321b47.bin
× × ×
1% Step3: Update device
START TO UPDATE
The second s
QUIT
A
HELP
Follow the belowing steps to update
Follow the belowing steps to update
Follow the belowing steps to update
Follow the belowing steps to update Re-pair Step 1: Choose a device to be paired NG SCAN BLUETOOTH
Follow the belowing steps to update Re-pair Step1: Choose a device to be paired NG
Follow the belowing steps to update Re-pair Step 1: Choose a device to be paired NG SCAN BLUETOOTH
Follow the belowing steps to update Re-pair Step1: Choose a device to be paired NG SCAN BLUETOOTH 2 Step2: Load the updated file RE-LOAD
Follow the belowing steps to update Re-pair Step1: Choose a device to be paired NG SCAN BLUETOOTH 2 Step2: Load the updated file RE-LOAD
Follow the belowing steps to update Re-pair Step1: Choose a device to be paired NG SCAN BLUETOOTH 2 Step2: Load the updated file RE-LOAD 3
Follow the belowing steps to update Re-pair Step1: Choose a device to be paired NG SCAN BLUETOOTH 2 Step2: Load the updated file RE-LOAD
Follow the belowing steps to update Re-pair Step1: Choose a device to be paired NG SCAN BLUETOOTH 2 Step2: Load the updated file RE-LOAD 3 Step3: Update device
Follow the belowing steps to update Re-pair Step1: Choose a device to be paired NG SCAN BLUETOOTH 2 Step2: Load the updated file RE-LOAD 3 Step3: Update device
Follow the belowing steps to update Re-pair Step1: Choose a device to be paired NG SCAN BLUETOOTH 2 Step2: Load the updated file RE-LOAD 3 Step3: Update device
Follow the belowing steps to update Re-pair Step1: Choose a device to be paired NG SCAN BLUETOOTH 2 Step2: Load the updated file RE-LOAD 3 Step3: Update device